MATERIAL SAFETY DATA SHEET PAGE: 1 DOW CHEMICAL U.S.A. MIDLAND MICHIGAN 48640 EMERGENCY PHONE: 517-636-4400

EFFECTIVE DATE: 15 JUN 81

PRODUCT CODE: 16822

PRODUCT NAME: CHLOROTHENE (R) VG SOLVENT

MSG: 0110

INGREDIENTS (TYPICAL VALUES-NOT SPECIFICATIONS)

1.1.1-TRICHLOROETHANE (NOMINAL)

SECTION 1

PHYSICAL DATA

BOILING POINT: 165F (74C) VAP PRESS: 100 MMHG & 200 VAP DENSITY (AIR=1): 4.55 : % VOLATILE BY VOL: 100 (ESSEN.)

: SOL. IN WATER: 0.07G/100G & 25C

: SP. GRAVITY: 1.320 3 25/25C

APPEARANCE AND ODOR: COLORLESS LIQUID.

SECTION 2

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: NONE : FLAMMABLE LIMITS (STP IN AIR) METHOD USED: T.O.G., T.C.C., C.O.C. : LFL: 7.5% 8 250 UFL: 15% 8 250 EXTINGUISHING MEDIA: WATER FOG. SPECIAL FIRE FIGHTING EQUIPMENT AND HAZARDS: SELF-CONTAINED RESPIRATORY EQUIPMENT. NOT CONSIDERED A FLAMMABLE LIQUID HAZARD UNDER AMBIENT TEMPERATURE USE CONDITIONS.

SECTION 3

REACTIVITY DATA

STABILITY: AVOID OPEN FLAMES. WELDING ARCS OR OTHER HIGH TEMPERATURE SOURCES WHICH INDUCE THERMAL DECOMPOSITION. INCOMPATIBILITY: WATER - SLOW HYDROLYSIS PRODUCES CORROSIVE ACID. HAZARDOUS DECOMPOSITION PRODUCTS: HYDROGEN CHLORIDE AND VERY SMALL AMOUNTS OF PHOSGENE AND CHLORINE. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 4 SPILL. LEAK. AND DISPOSAL PROCEDUPES

ACTION TO TAKE FOR SPILLS (USE APPROPRIATE SAFETY EQUIPMENT): SMALL LEAKS: MOP UP. WIPE UP OR SOAK IMMEDIATELY. REMOVE TO OUT OF DOORS. LARGE SPILLS: EVACUATE AREA. CONTAIN LIQUID; TRANSFER TO CLOSED METAL CONTAINERS. KEEP OUT OF WATER SUPPLIES.

DISPOSAL METHOD: (IN ORDER OF PREFERENCE) SEND SOLVENT TO LICENSED RECLAIMER. INCINERATION, EVAPORATION OF VERY SMALL QUANTITIES, OR APPROVED LANDFILL BURIAL IN COMPLIANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DUMPING INTO SEWERS. ON THE GROUND, OR INTO ANY BODY OF WATER IS STRONGLY DISCOUPAGED. AND MAY BE ILLEGAL.

(CONTINUED ON PAGE 2 )

(R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY